

vitra 689™

NEXT
GENERATION
PDT LASER



Red 689 nm Laser
for Photodynamic Therapy

vitra 689™

TECHNICAL SPECIFICATIONS

VITRA 689

Laser Source:	Semiconductor laser diode
Wavelength:	689 nm +/- 3 nm
Output Power:	Variable to meet 600 mW/cm ² at selected spot size
Maximum Power:	400 mW
Exposure Time:	83 s
Aiming beam:	650 nm
Size:	18 (H) x 19.5 (W) x 30 (D) cm 7.1" (H) x 7.7"(W) x 11.8"(D)
Weight:	5.6 kg – 12.3 lbs
Cooling:	Air
Power requirements:	100 to 240 VAC, 350 VA, 50/60 Hz

SLIT LAMP ADAPTERS

Slit lamp compatibility:	Quantel Medical slit lamp, Haag Streit 900 BM & BQ and clones
Zoom:	Motorized
Spot size:	Continuously adjustable from 1200 to 5400 µm (Up to 8000 µm with a magnifying contact lens)
Weight:	0.9 kg – 1.98 lbs

Designed and Manufactured by Quantel Medical in France
© 2019. Quantel Medical, Vitra 689® is trademark of Quantel Medical. All rights reserved.



www.quantel-medical.com



CE
0459



ISO 9001 : 2015 – ISO 13485 : 2016

Headquarters
Quantel Medical
11, rue du Bois Joli - CS40015
63808 Cournon d'Auvergne – FRANCE
Tel: +33 (0)4 73 745 745
Email: contact@quantel-medical.fr

North America
Quantel Medical USA
2313 Ridge Road Suite 105A
Rockwall, TX 75087 – USA
Tel: +1 888 660 6726
Email: info@quantelmedical.com

Poland
Quantel Medical
ul. Racławicka 93
02-634 Warszawa - POLAND
Tel: +48 22 5210111
Email : info@quantel-medical.pl

Representative Offices
Thailand, Chiang Mai
Brazil, Rio De Janeiro